Convolutional networks

Deep Learning: Bryan Pardo, Northwestern University, Fall 2020

How big is that image?



1000

How many weights in a fully connected net?



N = 1000

50,000,000 + 5,000 + 100 = 50,005,100 weights

How does the eye do this?



Image from https://askabiologist.asu.edu/rods-and-cones

Limited receptive fields, at multiple levels



Image from https://askabiologist.asu.edu/rods-and-cones

Small Fixed Windows (filter size/receptive field)

- If important features fall within a bounded size region, we can bound the receptive field of each unit to that size.
- This greatly reduces the number of weights.



Shared weights

- If a feature is good to find in one region, it may be good to find in other regions.
- Units look for the same feature if they share weights.
- A set of units that share weights is a feature map.











Multiple Feature Maps

- To look for multiple features, use multiple feature maps.
- Each map will specialize on one thing.
- Even with many feature maps, you still have far fewer weights



Stride

• How many units you move with each step of your filter/kernel









Padding

• Extra blank rows and columns added around your input.

















Dilation

• Space out the squares of the filter on your input.













Channels

RGB 3-color input has 3 channels



Convolutional layer with 5 channel output



Convolutional layer with 2 channel output



How many weights in a convolutional net?



15,000 + 15,000 + 50 = 30,050 unique weights

Compare that to the 50,005,100 weights in the other network

Is that enough reduction?

- That picture of the adorable Capybara was 500,000 pixels.
- The 2017 iPhone X takes 12 megapixel images. That's 24 times as big.
- Making the network on the previous slide 24 times bigger would have us at over 600,000 weights.
- Can we do some kind of down sampling on our data?































Other kinds of pooling

- Min pooling
- Average pooling
- When would you want to use each of these? How would you pick?

Reduce your patch size, if you can

- Use a small patch of the spectrogram as input (e.g. 100 by 100 patch of the spectrogram)
- Reduces the number of model parameters needed
- Increases the number of training examples

1000 Spectrograms * 600 patches* 100augmentations = 60 million

So...what is a convolutional net?

- A network with one or more layers that are feature maps
- A layer with feature maps is called a "convolutional layer"
- Often, convolutional layers are alternated with pooling layers.
- Since these nets have many fewer connections
 - They train faster
 - They need fewer training examples